EPOS

PC 7 USB

Single-sided USB headset

For those that want high quality audio while still being aware of their immediate surroundings, the PC 7 USB is the perfect headset choice, whether working from home, studying via e-learning, or simply staying in touch.

The single-sided design delivers high quality audio to one ear, while leaving the other free, so you can be sure of what is going on around you. The same single-sided format also ensures that the headset is comfortable and extremely light weight, and available at a highly competitive price point.

The USB connector makes connecting the headset to PC and Mac simple and fast, and a unidirectional noise-cancelling microphone minimizes background noise so your voice can be heard clearly. Durable design, meanwhile, means the PC 7 USB is built to last.

See more at eposaudio.com/pc-7-usb



Key benefits & features

Single-sided USB headset

Delivers clear, quality audio while keeping you aware of your surroundings

Plug-and-play simplicity

Connect quickly and effortlessly to PC or Mac via USB

Noise-cancelling microphone

Unidirectional microphone for crystal clear conversation

Lightweight and comfortable

Distraction-free comfort, even on the longest calls

Designed to last

Built to survive the rigors of daily use

EPOS

PC 7 USB

Product data

Ear coupling On-ear Transducer principle Dynamic, open Connectivity Wired, USB Sound Card Cable length 2 m Compatibility PC & Mac OSX Warranty 2 years, international Headphones Frequency response 42–17,000 Hz Impedance 32 Ω Sound pressure level 95 dB SPL @ 1 kHz, 1V RMS Microphone Frequency response 90 – 15,000 Hz Pick-up pattern Unidirectional Sensitivity -40 dBV/Pa	General	
Connectivity Wired, USB Sound Card Cable length 2 m Compatibility PC & Mac OSX Warranty 2 years, international Headphones Frequency response 42-17,000 Hz Impedance 32 Ω Sound pressure level 95 dB SPL @ 1 kHz, 1V RMS Microphone Frequency response 90 - 15,000 Hz Pick-up pattern Unidirectional Sensitivity -40 dBV/Pa	Ear coupling	On-ear
Cable length 2 m Compatibility PC & Mac OSX Warranty 2 years, international Headphones Frequency response 42-17,000 Hz Impedance 32 Ω Sound pressure level 95 dB SPL @ 1 kHz, 1V RMS Microphone Frequency response 90 - 15,000 Hz Pick-up pattern Unidirectional Sensitivity -40 dBV/Pa	Transducer principle	Dynamic, open
Compatibility PC & Mac OSX Warranty 2 years, international Headphones Frequency response 42–17,000 Hz Impedance 32 Ω Sound pressure level 95 dB SPL @ 1 kHz, 1V RMS Microphone Frequency response 90 – 15,000 Hz Pick-up pattern Unidirectional Sensitivity -40 dBV/Pa	Connectivity	Wired, USB Sound Card
Warranty 2 years, international Headphones Frequency response 42–17,000 Hz Impedance 32 Ω Sound pressure level 95 dB SPL @ 1 kHz, 1V RMS Microphone Frequency response 90 – 15,000 Hz Pick-up pattern Unidirectional Sensitivity –40 dBV/Pa	Cable length	2 m
Headphones Frequency response 42-17,000 Hz Impedance 32 Ω Sound pressure level 95 dB SPL @ 1 kHz, 1V RMS Microphone Frequency response Pick-up pattern Unidirectional Sensitivity -40 dBV/Pa	Compatibility	PC & Mac OSX
Frequency response 42-17,000 Hz Impedance 32 Ω Sound pressure level 95 dB SPL @ 1 kHz, 1V RMS Microphone Frequency response Pick-up pattern Unidirectional Sensitivity -40 dBV/Pa	Warranty	2 years, international
Impedance 32 Ω Sound pressure level 95 dB SPL @ 1 kHz, 1V RMS Microphone Frequency response 90 - 15,000 Hz Pick-up pattern Unidirectional Sensitivity -40 dBV/Pa	Headphones	
Sound pressure level 95 dB SPL @ 1 kHz, 1V RMS Microphone Frequency response 90 - 15,000 Hz Pick-up pattern Unidirectional Sensitivity -40 dBV/Pa	Frequency response	42-17,000 Hz
Microphone Frequency response 90 - 15,000 Hz Pick-up pattern Unidirectional Sensitivity -40 dBV/Pa	Impedance	32 Ω
Frequency response 90 - 15,000 Hz Pick-up pattern Unidirectional Sensitivity -40 dBV/Pa	Sound pressure level	95 dB SPL @ 1 kHz, 1V RMS
Pick-up pattern Unidirectional Sensitivity -40 dBV/Pa	Microphone	
Sensitivity -40 dBV/Pa	Frequency response	90 - 15,000 Hz
	Pick-up pattern	Unidirectional
Impedance 2,200	Sensitivity	-40 dBV/Pa
	Impedance	2,200

Packaging		
Dimension of product packaging (W x H x D)	212 x 244 x 64.5 mm	
Package weight (incl. complete product and packaging)	180 g	
Dimension of inner master carton (W x H x D)	250 x 230 x 80 mm	
Dimension of master carton (L x W x H)	480 x 382 x 520 mm	
Units in distributor master carton	20	
Languages	English, German, French, Spanish, Russian, Japanese	

EP3S 3/3

PC 7 USB

Product overview

Product	Art. no.	Description	EAN / UPC code
PC 7 USB	1000431	Single-sided USB headset	EAN: 57 14708 00232 1 UPC: 8 40064 40232 3